

### Overview

#### HPE SN1600 Series 32Gb Fibre Channel Host Bus Adapter

The HPE 32Gb Fibre Channel Host Bus Adapters are designed to support ProLiant Servers with PCI-Express I/O slots to connect to Hewlett Packard Enterprise Storage Arrays using the 32/16/8 Gb Fibre Channel protocol.

The HPE 32GFC Host Bus Adapters bring datacenter infrastructure components to a higher level of performance and efficiency with the ability to deliver twice the bandwidth performance of 16Gb HBAs at lower latency. A 32GFC HBA purchased today is backward compatible with 16Gb and 8Gb storage networks and will protect future investments. When using storage intensive applications, such as backup/restore, database transactions, virtualization, and rich media, the increased performance of the 32GFC infrastructure enables rapid storage and retrieval of critical information. Designed for environments with greater virtual machine density and bandwidth requirements, the 32GFC HBAs enable more applications and VMs to run on a single host server and Fibre Channel port, resulting in reduced cabling and a higher return on IT investment. Enhanced diagnostics and orchestration capabilities make 32Gb Fibre Channel adapters well suited for to deliver on SLA requirements and application performance.

#### Models

##### Description

##### SKU

##### Single Port

###### SN1610Q

HPE SN1610Q 32Gb 1-port Fibre Channel Host Bus Adapter

R2E08A

###### SN1610E

HPE SN1610E 32Gb 1-port Fibre Channel Host Bus Adapter

R2J62A

###### SN1600Q

HPE SN1600Q 32Gb Single Port Fibre Channel Host Bus Adapter

P9M75A

###### SN1600E

HPE SN1600E 32Gb Single Port Fibre Channel Host Bus Adapter

Q0L11A

##### Dual Port

###### SN1610Q

HPE SN1610Q 32Gb 2-port Fibre Channel Host Bus Adapter

R2E09A

###### SN1610E

HPE SN1610E 32Gb 2-port Fibre Channel Host Bus Adapter

R2J63A

###### SN1600Q

HPE SN1600Q 32Gb Dual Port Fibre Channel Host Bus Adapter

P9M76A

###### SN1600E

HPE SN1600E 32Gb Dual Port Fibre Channel Host Bus Adapter

Q0L12A

#### What's New

- FC-NVMe support in Windows, VMware and Linux OSes

---

## Standard Features

### Key Features and Benefits

#### Performance

Up to two ports of 32Gb FC delivers Up to 5 million IOPS and 12,800MBps bandwidth across two 32GFC ports. Enhanced reliability, diagnostics, and accelerated deployment powered by 32Gb Fibre Channel ASIC.

Advanced integration with HPE B-series 16Gb and 32Gb fabrics to speed SAN deployment and configuration, speed and simplify SAN diagnostics, improve SAN resiliency and Quality of Service.

Best combination of Fibre Channel IOPS, latency and throughput performance enables increased application and database transactions per second, enables faster large block transfers and increases the number of VMs that can be supported per server.

---

#### PCIe 4.0

The HPE SN1610Q & SN1610E HBAs are PCIe 4.0 ready

---

#### Support for greater Server Virtualization

Higher bandwidth and ability to virtualize physical ports with QoS in the adapter, make these adapters ideal for high density server virtualization environments for increased scalability. Enables more applications and VMs to run on a single server and Fibre Channel port, resulting in reduced cabling and a higher return on IT investment.

---

#### Connectivity to HPE Server and Storage

Provides an HPE-branded HBA solution which has undergone extensive HPE interoperability testing for connecting HPE ProLiant and Apollo servers into HPE Storage and networking environments.

---

#### LUN Prioritization and QoS

HPE 32Gb FC HBAs support Class Specific Control (CS\_CTL) which allows prioritization and bandwidth allocation at the LUN level. In addition, the SN1610Q and SN1610E adapters support Virtual Machine ID (VM-ID) which further enhances prioritization and monitoring to the virtual machine within the SAN, providing a VM-aware storage network. These features are managed using the management software, downloadable from [HPE Software Downloads](#).

---

#### FC-NVMe Ready

HPE 32Gb Fibre Channel Host Bus Adapters are NVMe-enabled to support emerging NVM Express (NVMe) over Fibre Channel storage networks. The HBAs are capable of running both SCSI protocol and NVME protocol on the same wire at the same time.

- FC-NVMe support in Windows Server 2016 / 2019 with Native Multipathing (Asymmetric namespace access (ANA)) and Boot from SAN (BFS) for SN1600Q, SN1610Q adapters
  - FC-NVMe support for ESX 7.0 U1, RHEL 8.3, RHEL 7.9, SLES 15 SP2 for SN1600Q, SN1610Q adapters
  - Supports FC-NVMe-2 Sequence Level Error Recovery (SLER)
- 

#### Active Health System

All HPE 32GFC adapters support HPE ProLiant Active Health System integration. This helps administrators accurately troubleshoot and resolves problem within the server faster.

---

#### Smart SAN support

Smart SAN is a protocol agnostic application embedded in SAN components that enables the 3PAR to orchestrate configuration, settings and policies in a SAN. HPE Smart SAN's Target Driven Zoning enables you to configure zones accurately in minutes and not in hours and its automatic discovery mechanism creates a powerful platform which would enable real-time diagnostics with self-healing in the near future.

---



## Standard Features

### Secure Firmware download

The SN1610Q and SN1610E delivers enhanced security via the new secure firmware update feature which protects and ensures the authenticity of device firmware.

---

### T10 Protection Information (T10-PI)

HPE 32GFC adapters support T10-PI for enhanced data integrity when connected to T10-PI enabled arrays like HPE 3PAR StoreServ.

---

### Forward error correction (FEC)

FEC is enabled and improved at 32GFC as required by the FC Specification, automatically correcting transmission errors and improving network performance and resiliency.

---

### Class-specific Control (CS\_CTL)

QoS capability that enables administrators to prioritize storage traffic to meet the needs of critical VM workloads.

---

### Link cable beaconing (LCB)

LED beaconing for ports on both ends of a physical link simplifies cable identification and management.

---

### D-Port Diagnostics

Quickly run automated diagnostic tests in a single step, across multiple adapters, servers, and fabric components to assess connectivity. Optics and cable problems are identified and resolved.

---

### FDMI,FC Ping, FC Trace Route

Quickly check connectivity to SAN devices and query the switch management server for in-depth details on connected devices.

---

### Read Diagnostic Parameters (RDP)

Identify the source of network and media errors like cyclic redundancy check (CRC) and loss of sync (LOS) by remotely accessing diagnostic information from anywhere in the fabric.

---

### Fabric-assigned Port Worldwide Name (FA\_WWN)

Administrators can preconfigure WWN settings at the switch port allowing Fibre Channel adapter to acquire port WWN address from the 16Gb or 32GFCfabric. This allows SAN administrator to configure SAN zoning without need for servers to be present.

---

### Fabric-based Boot LUN (F\_BLD)

Allows Boot-LUN information directly from 16Gb or 32GFCswitch, speeding up deployment of new servers in a SAN environment.

---

### Firmware Integrity Protection With Hardware Root of Trust

The HPE SN1610Q & SN1610E 32Gb FC HBAs incorporate a hardware RoT that keeps malicious firmware from hijacking the adapter. The adapters RoT enables both integrity and authenticity during adapter firmware updates by both validating firmware embedded signatures with hardware embedded keys to ensure that only bona fide firmware executes, and protecting firmware updates that are applied over public networks.

---



## Standard Features

### Brocade Port Trunking

SN1610E port aggregation capability (also known as trunking) provides a method to aggregate physical ports together to form a single logical port. Aggregating physical ports to make a single high-bandwidth data path increases the logical connection bandwidth for applications that need it, such as data warehousing and virtual machine migration.

---

### Universal SAN Congestion Mitigation (USCM)

USCM support (Fabric Performance Impact Notifications, FPIN) for SN1600Q, SN1610Q in the following tools & OS distros:

- QCC CLI, ESX CLI, Windows / Linux / ESX drivers
  - USCM I/O Throttling mitigation support
- 



## Service and Support

### HPE Support Services and Warranty Information

#### Protect your business beyond warranty with HPE Support Services

HPE Technology Services delivers confidence, reduces risk and helps customers realize agility and stability. Our integrated portfolio of Services for storage help customers reduce costs, optimize data, streamline storage management, and improve backup and recovery. HPE Support Services enable you to choose the right service level, length of coverage and response time as you purchase your new storage solution, giving you full entitlement for the support for need for your IT and business.

---

#### Recommended Services

Support for this adapter is at the level of server it is a part of. Please check the quick specs of the server.

---

#### Parts and Materials

Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by Hewlett Packard Enterprise due to malfunction.

---

#### Learn More

To learn more on HPE Storage Services, please contact your Hewlett Packard Enterprise sales representative or Hewlett Packard Enterprise Authorized Channel Partner

HPE Support Services are sold by Hewlett Packard Enterprise and Hewlett Packard Enterprise Authorized Service Partners.

<http://www.hpe.com/services>

---

#### Warranty

3-0-0 Three-year parts exchange warranty. Additional warranty protection can be purchased.

HPE Global Services provides a three-year, limited warranty, fully supported by a worldwide network of resellers and service providers and toll-free 7 x 24 hardware technical phone support for the duration of the warranty. In addition, available service offerings include a full range of HPE Pointnext operational packaged hardware and software services.

**Notes:** Certain restrictions and exclusions apply. Consult the HPE Customer Support Center for details.

---



## Technical Specifications

### Family Information

	R2E08A	R2E09A	R2J62A	R2J63A
<b>Number of channels</b>	Single	Dual	Single	Dual
<b>Port Speed</b>	32GFC	32GFC	32GFC	32GFC
<b>OS Supported</b>	<b>Notes:</b> Always refer to the HPE Single Point of Connectivity Knowledge for HPE Storage Products at: <a href="http://www.hpe.com/storage/spock">http://www.hpe.com/storage/spock</a> for specific product support information and specific OS versions supported.			
<b>Microsoft Windows Server 2019/2016 &amp; HyperV</b>	x64	x64	x64	x64
<b>RHEL 8.x, 7.x</b>	x64	x64	x64	x64
<b>VMware ESX/ESXi 7.0,6.7, 6.5</b>	x64	x64	x64	x64
<b>SLES 15.x, 12.x</b>	x64	x64	x64	x64
<b>Servers Supported</b>	Select HPE ProLiant and Apollo Gen10 servers <b>Notes:</b> Refer to server Quick Specs for details regarding supported options.			
<b>Array Platforms Supported</b>	Refer to <a href="http://www.hpe.com/storage/spock">http://www.hpe.com/storage/spock</a> for specific product support information			
<b>What's Included in the Box?</b>	32 Gbps HBA with standard bracket, one 32 Gbps SFP+ transceiver, low-profile bracket, documentation	32 Gbps HBA with standard bracket, two 32 Gbps SFP+ transceiver, low-profile bracket, documentation	32 Gbps HBA with standard bracket, one 32 Gbps SFP+ transceiver, low-profile bracket, documentation	32 Gbps HBA with standard bracket, two 32 Gbps SFP+ transceiver, low-profile bracket, documentation
<b>Environmental Operating Temperature</b>	32° F to 131° F 0° C to 55° C		32° F to 131° F 0° C to 55° C	
<b>Environmental Storage Temperature</b>	-4° F to 158° F (-20° C to 70° C)		-4° F to 185° F (-20° C to 85° C)	
<b>Environmental Relative Humidity Operating</b>	10% to 90% RH at 40° C (non-condensing)		5% to 95% (non-condensing)	
<b>Product Dimensions (W x D x H)</b>	6.6 x 0.49 x 2.73 in (167.64 x 12.44 x 69.34mm)		6.6 x 0.43 x 2.71 in (167.64 x 10.92 x 68.83mm)	
<b>Media</b>	Multi-mode Optic (SFP+)		Multi-mode Optic (SFP+)	
<b>Connector</b>	Short wave laser with LC type connector		Short wave laser with LC type connector	
<b>PCIe Connector</b>	PCIe 4.0 x8		PCIe 4.0 x8	
<b>Auto-negotiation</b>	32/16/8 Gbps		32/16/8 Gbps	



## Technical Specifications

	P9M75A	P9M76A	Q0L11A	Q0L12A
<b>Number of channels</b>	Single	Dual	Single	Dual
<b>Port Speed</b>	32GFC	32GFC	32GFC	32GFC
<b>OS Supported</b>	<b>Notes:</b> Always refer to the HPE Single Point of Connectivity Knowledge for HPE Storage Products at: <a href="http://www.hpe.com/storage/spock">http://www.hpe.com/storage/spock</a> for specific product support information and specific OS versions supported.			
<b>Microsoft Windows Server 2019/2016/2012/2012 R2 &amp; HyperV</b>	x64	x64	x64	x64
<b>RHEL 8.x, 7.x, 6.x</b>	x64	x64	x64	x64
<b>VMware ESX/ESXi 7.0, 6.5, 6.0</b>	x64	x64	x64	x64
<b>SLES 15.x,12.x, 11.x</b>	x64	x64	x64	x64
<b>Servers Supported</b>	Select HPE ProLiant and Apollo Gen10 & Gen9 servers <b>Notes:</b> Refer to server Quick Specs for details regarding supported options.			
<b>Array Platforms Supported</b>	Refer to <a href="http://www.hpe.com/storage/spock">http://www.hpe.com/storage/spock</a> for specific product support information			
<b>What's Included in the Box?</b>	32 Gbps HBA with standard bracket, one 32 Gbps SFP+ transceiver, low-profile bracket, documentation	32 Gbps HBA with standard bracket, two 32 Gbps SFP+ transceiver, low-profile bracket, documentation	32 Gbps HBA with standard bracket, one 32 Gbps SFP+ transceiver, low-profile bracket, documentation	32 Gbps HBA with standard bracket, two 32 Gbps SFP+ transceiver, low-profile bracket, documentation
<b>Environmental Operating Temperature</b>	32° F to 131° F 0° C to 55° C 110 LFPM at 55° C		32 F to 131° F 0° C to 55° C	
<b>Environmental Storage Temperature</b>	-4° F to 158° F (-20° C to 70° C)		-4° F to 185° F (-20° C to 85° C)	
<b>Environmental Relative Humidity Operating</b>	10% to 90% RH at 40° C (non-condensing)		10% to 90% RH at 40° C (non-condensing)	
<b>Product Dimensions (W x D x H)</b>	6.59 x 0.49 x 4.38 in (12.34x167.51x111.25mm)		6.6 x 0.69 x 2.71 in (167.6 x 17.5 x 68.9 mm)	
<b>Media</b>	Multi-mode Optic (SFP+)		Multi-mode Optic (SFP+)	
<b>Connector</b>	Short wave laser with LC type connector		Short wave laser with LC type connector	
<b>PCIe Connector</b>	PCIe 3.0 x8			
<b>Auto-negotiation</b>	32/16/8 Gbps			



## Summary of Changes

Date	Version History	Action	Description of Change
04-May-2021	Version 13	Changed	Added FC-NVMe OS support
03-Aug-2020	Version 12	Changed	Added SN1610E details
15-Jun-2020	Version 11	Changed	Overview and Technical Specifications sections were updated.
02-Dec-2019	Version 10	Changed	Standard Features section was updated.
21-Oct-2019	Version 9	Changed	Standard Features section was updated.
07-Oct-2019	Version 8	Changed	SN1610Q adapters
07-Jan-2019	Version 7	Changed	Feature information edited with latest information Overview and Service and Support sections were updated
18-Dec-2017	Version 6	Changed	Overview section was revised.
07-Aug-2017	Version 5	Changed	Added Gen10 server support
08-May-2017	Version 4	Changed	Changes made throughout the document
24-Feb-2017	Version 3	Changed	Feature and table of specifications are cleaned up with latest information
28-Nov-2016	Version 2	Changed	32Gb SN1600E Single Port and Dual Port adapters added
26-Sep-2016	Version 1	New	New QuickSpecs





## Copyright

Make the right purchase decision.  
Contact our presales specialists.



Chat



Email



Call



Get updates



**Hewlett Packard**  
Enterprise

© Copyright 2021 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

c05205227 - 15650 - Worldwide - V13 - 04-May-2021