

### Overview

#### HPE OfficeConnect OC20 802.11ac Series Access Points

HPE OfficeConnect OC20 802.11ac Series Access Points (AP) offer small businesses an intuitive and cost-effective wireless solution that is easy to set-up and manage without technical expertise. By using the OfficeConnect iOS or Android mobile application customers can get their Wi-Fi network up and running within minutes and monitor the network remotely, no matter where they might be.

The OC20 APs deliver aggregate speeds up to 1.3Gbps and reliable connectivity to handle today's business critical voice, video and cloud applications. The OfficeConnect Smart Air software intelligently optimizes wireless coverage and performance, mitigates interference and automatically connects users to the best AP for a great end-user experience. Customers can scale and centrally manage up to eight APs using clustering making ongoing network changes and maintenance a snap.

To support highly secure visitor and guest access the OC20 APs offer a captive portal for guest with multiple authentication options including Facebook Wi-Fi social log-ins and the ability to schedule access based on specific days and times of day.

The HPE OfficeConnect OC20 wireless APs come with integrated application filtering that provides comprehensive protection against online threats and blocks inappropriate content. They also safeguard sensitive business information using Wi-Fi Protected Access 2 (WPA2) and advanced encryption. The product includes a 3-year Warranty with 24x7 phone support for 90 days.

---



**HPE OfficeConnect OC20 802.11ac Series Access Points**

---

## Overview

### Models

HPE OfficeConnect OC20 2x2 Dual Radio 802.11ac (US) Access Point

JZ073A

HPE OfficeConnect OC20 2x2 Dual Radio 802.11ac (RW) Access Point

JZ074A

---

### Key features

- Fast, reliable 2x2 802.11ac wireless connectivity designed for small business
  - OfficeConnect Mobile app for easy and quick set up of employee and guest Wi-Fi network
  - Create a network of up to eight access points, manage and monitor from mobile app, on the go
  - Captive portal for secure guest access with Facebook Wi-Fi social media log-in
  - Built-in application filtering categories – set guidelines to protect your business from online threats and inappropriate websites
  - HPE 3-year Warranty
-

## Standard Features

### Features and benefits

#### Dual Radio 802.11ac Access Point

Supports up to 867 Mbps in the 5GHz band (with 2SS/VHT80 clients) and up to 400 Mbps in the 2.4GHz band (with 2SS/VHT40 clients).

---

#### Smart Air for RF Management

Smart Air software automatically assigns channel and power settings, provides airtime fairness (boosts overall network performance by allowing faster clients to move quicker on the network) and ensures that APs stay clear of RF interference to deliver a reliable, high-bandwidth wireless network

---

#### Security

Application filtering identifies, classifies, and blocks access to applications and web content to provide comprehensive protection against advanced online threats.

WPA2 with advanced encryption keeps your network traffic secure and protects sensitive business information.

---

#### Management

The OfficeConnect iOS or Android mobile applications allows you to set-up an employee and guest network in easy steps.

New APs added to the network automatically get their configuration from the first AP without manual configuration; create a network of up to eight APs and manage from the OfficeConnect mobile application.

Remotely monitor the network with a quick health dashboard that provides visibility into the status of the access points, their signal strength, connected users and web applications.

---

#### Warranty

3-year Warranty

This series comes with a 3-year Warranty providing advance hardware replacement with next business day shipment in most countries, 24x7 phone support available for the first 90 days, and online chat support for the entire warranty period. See [hpe.com/networking/warrantysummary](http://hpe.com/networking/warrantysummary) for full warranty and support information included with your product purchase.

---

#### Mounting

The AP ships with two (white) mounting clips to attach to a 9/16-inch or 15/16-inch flat T-bar drop-tile ceiling.

Several optional mount kits are available to attach the AP to a variety of surfaces; see the Ordering Information section above for detail.

---

## Configuration Information

### Build To Order:

**BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.**

Remarks	Description	SKU
	HPE OfficeConnect OC20 2x2 Dual Radio 802.11ac (US) Access Point	JZ073A
	HPE OfficeConnect OC20 2x2 Dual Radio 802.11ac (RW) Access Point	JZ074A
	HPE OfficeConnect OC20 2x2 Dual Radio 802.11ac (JP) Access Point	JZ110A
	HPE OfficeConnect OC20 2x2 Dual Radio 802.11ac (IL) Access Point	JZ111A
	HPE OfficeConnect OC20 2x2 Dual Radio 802.11ac (EG) Access Point	JZ112A

### Power Options

Std (Min 0 // max 1) User Selection (min 0 // max 1) per AP		
Aruba PD-9001GR-AC 30W 802.3at PoE+ 10/100/1000 Ethernet Indoor Rated Midspan Injector		JW629A
Aruba PD-3510G-AC 15.4W 802.3af PoE 10/100/1000Base-T Ethernet Midspan Injector		JW627A
AP-AC-12V30B 12V/30W AC/DC Desktop Style 2.1/5.5/9.5mm Circular 90 Deg Plug DoE Level VI Adapter		JX990A
AP-AC2-12B 12V/36W AC/DC desktop style power adapter with type B connector		R3K00A

**NOTE:** If this Power Supply is selected, bring in (Min 1 // Max 1) Localized power cord based on the Aruba Localization Menu.  
The AP device is usually PoE powered from the switch, therefore, these Power Adapter are optional.

### Accessories

#### AP Mount Kits

Remarks	Description	SKU
	Std (Min 0 // max 99) User Selection (min 0 // max 99)	
	AP-220-MNT-C2 2x Ceiling Grid Rail Adapter for Interlude and Silhouette Mt Kit	JW045A
	AP-220-MNT-W1 Flat Surface Wall/Ceiling Black AP Basic Flat Surface Mount Kit	JW046A
	AP-220-MNT-W1W Flat Surface Wall/Ceiling White AP Basic Flat Surface Mount Kit	JW047A
	AP-200-MNT-W3 White Low Profile Box Style Secure Small Indoor AP Flat Surface Mount Kit	JY705A
	AP-MNT-CM1 Industrial Grade Indoor Access Point Metal Suspended Ceiling Rail Mount Kit	JX961A

**NOTE:** OC220 AP Unit ships with basic suspended ceiling rail clips (JW044A)

#### Accessories

Std (Min 0 // max 99) User Selection (min 0 // max 99)		
AP-CBL-ETH10 10-pk Short Ethernet Cable		JW072A

## Technical Specifications

### I/O ports and slots

- One 10/100/1000BASE-T Ethernet network interface (RJ-45)
    - Auto-sensing link speed and MDI/MDX
    - 802.3az Energy Efficient Ethernet (EEE)
  - Visual indicators (multi-color LEDs): for System and Radio status
  - Reset button: factory reset (during device power up)
  - Kensington security slot
- 

### Wi-Fi Radio Specifications

- Indoor, dual radio, 5GHz 802.11ac 2x2 MIMO and 2.4GHz 802.11n 2x2 MIMO
  - Connectivity standard IEEE 802.11 a/b/g/n/ac
  - Support for up to 100 associated client devices per radio
  - Supported frequency bands (country-specific restrictions apply)
    - 2.400 to 2.4835GHz
    - 5.150 to 5.250GHz
    - 5.250 to 5.350GHz
    - 5.470 to 5.725GHz
    - 5.725 to 5.850GHz
  - Available channels: Dependent on configured regulatory domain
  - Short guard interval for 20MHz, 40MHz and 80MHz channels
  - Space-time block coding (STBC) for increased range and improved reception
  - Low-density parity check (LDPC) for high-efficiency error correction and increased throughput
  - Transmit beam-forming (TxBF) for increased signal reliability and range
  - Supported data rates (Mbps):
    - 802.11b: 1, 2, 5.5, 11
    - 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54
    - 802.11n: 6.5 to 300 (MCS0 to MCS15)
    - 802.11ac: 6.5 to 867 (MCS0 to MCS9, NSS = 1 to 2 for VHT20/40/80)
- 

### Wi-Fi Antennas

Two integrated dual-band downtilt omni-directional antennas for 2x2 MIMO with maximum antenna gain of 3.4dBi in 2.4GHz and 6.6dBi in 5GHz.

---

### Physical characteristics

- **Dimensions**  
5.9 x 5.9 x 1.6 in (5.9 x 5.9 x 1.6 in)
  - **Weight**  
0.8 lbs (380 g)
- 

### Power sources and consumption

The AP supports direct DC power and Power over Ethernet (PoE)

- When both power sources are available, DC power takes priority over PoE
  - Power sources are sold separately
  - Direct DC source: 12Vdc nominal, +/- 5%
  - Power over Ethernet (PoE): 48 Vdc (nominal) 802.3af/802.3at compliant source
  - Maximum (worst-case) power consumption: 12.3W (PoE) or 10.1W (DC)
  - Maximum (worst-case) power consumption in idle mode: 5.3W (PoE) or 4.4W (DC)
-

## Technical Specifications

### Environment

- **Operating temperature**  
0° C to +50° C (+32° F to +122° F)
  - **Operating humidity**  
5% to 95% non-condensing
  - **Storage & transportation**  
-40° C to +70° C (-40° F to +158° F)
- 

### Regulatory

- FCC/Industry of Canada
  - CE Marked
  - RED Directive 2014/53/EU
  - Low Voltage Directive (2014/35/EU)
  - EN 300 328
  - EN 301 489
  - EN 301 893
  - UL/IEC/EN 60950
  - EN 60601-1-1, EN60601-1-2
- 

### Certifications

- CB Scheme Safety, cTUVus
  - UL2043 plenum rating
  - Wi-Fi Alliance (WFA) certified 802.11a/b/g/n/ac
- 

### Warranty

- 3-year warranty
-

## Summary of Changes

Date	Version History	Action	Description of Change:
04-Nov-2019	Version 3	Changed	Configuration Information section was updated. New SKUs were added.
04-Sep-2017	Version 2	Changed	Configuration section was updated
03-Jul-2017	Version 1	New	New QuickSpecs



© Copyright 2019 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

a00016709enw - 15972 - Worldwide - V3 - 04-November-2019