

# QuickSpecs

## HPE OfficeConnect M220 802.11n Access Point Series

### Overview

### HPE OfficeConnect M220 802.11n Access Point Series



### Models

HPE OfficeConnect M220 802.11n (AM) Access Point

J9798A

HPE OfficeConnect M220 802.11n (WW) Access Point

J9799A

### Key features

- IEEE 802.11a/b/g/n access point
- Single-radio, dual-band (2.4 GHz or 5 GHz)
- Simplified wireless LAN administration with clustering technology
- Powered by IEEE 802.3af PoE or included power supply
- Limited Lifetime Warranty

### Product overview

HPE OfficeConnect M220 802.11n Access Point Series are cost effective access points ideal for small businesses requiring multiple access points for wireless coverage. They support standalone operation as well as "clustering" of up to 16 access point to accommodate wireless coverage of mid-size locations. HPE OfficeConnect M220 Access Points are dual-band, single-radio devices supporting high-speed wireless networking at 5GHz or 2.4GHz. Dual-band operation gives you flexibility to use the less congested 5GHz spectrum for better wireless performance, better user experience and faster delivery of mobile applications. They are fully compatible with the high-speed IEEE 802.11n wireless standard and backward-compatible for legacy IEEE 802.11a/b/g support.

With clustering technology, a configuration change on one access point propagates across all HPE OfficeConnect M220 Access Points so changes are uniform throughout the network for consistent security and uninterrupted wireless client roaming. Clustering technology requires no wireless controller or additional hardware, enabling you to keep your network easily accessible. The series is part of the OfficeConnect portfolio of Hewlett Packard Enterprise small business wireless networking products.

## Overview

HPE OfficeConnect M220 802.11n Access Point Series includes a Limited Lifetime Warranty. This warranty includes advance hardware replacement with next business day shipment in most countries, limited 24x7 telephone support available from HPE for the first 90 days, and limited electronic and business hours telephone support is available from HPE for the entire warranty period.

## Features and benefits

### Management

- **Centralized wireless LAN management (clustering)**
  - **Simplified access point management**  
configuration parameters enabled on one access point pass to all members (up to 10 APs) of the cluster, eliminating the need to individually configure each AP
  - **Auto channel planning**  
access points in a cluster are automatically assigned to a channel that reduces interference between adjacent APs
  - **Client connection list**  
access any member of the cluster to view information about clients connected to any clustered AP
- **Secure and easy-to-use Web UI**
  - **Quick setup page**  
consolidates key settings into one page for simple and rapid configuration for common deployment scenarios
  - **HTTPS secured management sessions**  
prevent management sessions from being observed on the network

### Connectivity

- **Fully IEEE 802.11n-compliant dual-band access point**
  - **2.4 GHz frequency band support**  
uses your IEEE 802.11n wireless clients alongside legacy IEEE 802.11b/g devices
  - **5 GHz frequency band support**  
operates your IEEE 802.11n and 802.11a devices in the 5 GHz spectrum, which has less interference from microwave ovens, Bluetooth devices, and cordless phones
- **IEEE 802.3af PoE-powered device (PD) option**  
simplifies deployment and dramatically reduces installation costs by helping to eliminate the time and cost involved in supplying local power at each access point location
- **Auto-MDIX**  
automatically adjusts for straight-through or crossover cables on the 10/100/1000 port
- **Spanning Tree Protocol (IEEE 802.1D)**  
prevents network loops
- **IPv6 support**  
The HPE OfficeConnect M220 802.11n Access Point provides native support for IPv6, the newest version of the Internet Protocol, as well as the previous IPv4 standard

### Mobility

- **Service-class segmentation**
  - **Up to 8 SSIDs**  
allows administrator to identify multiple service sets for clients to access.
  - **Up to 8 VLANs**  
IEEE 802.1Q VLAN tagging provides security and traffic control between workgroups.
  - **SSID to VLAN mapping**  
permits segmenting traffic on each SSID to a specific VLAN.
- **Auto channel select**  
helps reduce radio co-channel interference by automatically selecting an unoccupied radio channel

## Overview

- **2x3:2 MIMO support**  
provides up to 300 Mbps performance and supports a maximum of 64 wireless clients per AP.
- **Wireless Distribution System (WDS)**  
allows HPE OfficeConnect M220 802.11n Access Points to connect wirelessly to other HPE OfficeConnect M220 802.11n Access Points without a wired backbone; this is useful for extending the network across areas where no wired infrastructure exists.
- **Interoperability**  
meets Wi-Fi Alliance certifications, including IEEE 802.11n Wi-Fi and WPA2 to help provide multivendor interoperability

## Security

- **Rogue AP detection**  
identifies all APs in range; known or trusted access points can be saved, allowing network administrators to identify unauthorized APs.
- **Secure Sockets Layer (SSL)**  
encrypts all HTTP traffic, allowing secure access to the browser-based management interface of the access point
- **Management password**  
provides security so that only authorized access to the Web browser interface is allowed
- **RADIUS-based user authentication**  
authenticates a user with a RADIUS server based on user credentials
- **RADIUS-based MAC authentication**  
authenticates a wireless client with a RADIUS server based on the MAC address of the client; this is useful for clients with minimal or no user interface
- **RADIUS-based VLAN assignment**  
places wireless client on RADIUS-assigned VLAN
- **Closed system**  
restricts broadcast of SSID as a security measure to conceal presence of the wireless network
- **Wired Equivalent Privacy (WEP) using 64- and 128-bit encryption**  
provides backward compatibility for legacy clients
- **Choice of IEEE 802.11i, WPA2, or WPA**  
locks out unauthorized wireless access by authenticating users prior to granting network access; robust Advanced Encryption Standard (AES) or Temporal Key Integrity Protocol (TKIP) encryption secures the data integrity of wireless traffic
- **Local wireless bridge client traffic filtering**  
prevents communication between wireless devices associated with the same access point

## Warranty and support

- **Limited Lifetime Warranty**  
This series comes with a Limited Lifetime Warranty providing advance hardware replacement with next business day shipment in most countries, 24x7 phone support available for the first 90 days, and electronic and business hours phone support for the entire warranty period. See <http://www.hpe.com/networking/warrantysummary> for full warranty and support information included with your product purchase.

## Configuration

### Build To Order:

BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

#### BTO Models

HPE OfficeConnect M220 802.11n (AM) Access Point

- 1 RJ-45 autosensing 10/100 ports

J9798A

See Configuration

**NOTE:1, 3**

No Power Cord

- No Localized Power Cord Selected

J9798A#AC3

HPE OfficeConnect M220 802.11n (WW) Access Point

- 1 RJ-45 autosensing 10/100/1000 ports

J9799A

See Configuration

**NOTE:2, 3**

No Power Cord

- No Localized Power Cord Selected

J9799A#AC3

#### Configuration Rules:

**Note 1** Only available in AMS. (Warning in Clic only)

**Note 2** Not available in AMS or Japan. (Warning in Clic only)

**Note 3** Localization required. (See Localization Menu)

### Power Supplies

None

### Access Point Options

#### External Power Supplies

HP 1-port Power Injector

J9407B

See Configuration

**NOTE:1**

#### Configuration Rules:

**Note 1** Localization required. (See Localization Menu)

## Technical Specifications

### HPE OfficeConnect M220 802.11n (AM) Access Point (J9798A)

<b>Ports</b>	1 RJ-45 autosensing 10/100/1000 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
<b>AP characteristics</b>	<b>Radios</b>	802.11a/b/g/n
	<b>Radio operation modes</b>	Client access, Client bridge
	<b>AP operation modes</b>	Autonomous
	<b>Wi-Fi Alliance Certification</b>	a/b/g/n Wi-Fi Certified
	<b>Physical characteristics</b>	<b>Dimensions</b>
	<b>Weight</b>	0.75 lb (0.34 kg)
	<b>Enclosure</b>	Indoor
<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C), noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	15% to 95% @ 149°F (65°C), noncondensing
	<b>Altitude</b>	up to 15,000 ft (4.6 km)
	<b>Acoustic</b>	Low-speed fan: 0 dB, High-speed fan: 0 dB (no fan)
<b>Electrical characteristics</b>	<b>Description</b>	IEEE 802.3af PoE Compliant or included 110-240 V 50/60 Hz external power supply
	<b>Voltage</b>	100 - 240 VAC, rated
	<b>Current</b>	0.4 A
	<b>Maximum power rating</b>	4.8 W
	<b>PoE power</b>	7 W PoE
	<b>Notes</b>	PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS). 5.3 watts is the maximum power draw when the device is used with the included power adapter.
	<b>Frequency band and operating channels</b>	<b>US</b>
<b>Radio</b>	FCC Part 15.247; FCC Part 15.407 (no DFS); RSS-210, Issue 8; RSS-Gen, Issue 3	
<b>Safety</b>	UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition	
<b>RF Exposure</b>	Canada RSS-102; FCC Bulletin OET-65 Supplement C	
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office	

### HPE OfficeConnect M220 802.11n (AM) Access Point (J9798A)

**QuickSpecs**

**HPE OfficeConnect M220 802.11n Access Point Series**

**Technical Specifications**

**IEEE 802.11n 5 GHz @ 20 MHz**

Data rate	MCS 0 Mbps	MSC 7 Mbps	MSC 8 Mbps	MSC 15 Mbps
Receiver sensitivity	-86 dBm	-67 dBm	-86 dBm	-68 dBm
Transmit power	15 dBm	11 dBm	15 dBm	11 dBm

**IEEE 802.11n 5 GHz @ 40 MHz**

Data rate	MCS 0 Mbps	MSC 7 Mbps	MSC 8 Mbps	MSC 15 Mbps
Receiver sensitivity	-83 dBm	-64 dBm	-84 dBm	-65 dBm
Transmit power	15 dBm	11 dBm	15 dBm	11 dBm

**IEEE 802.11n 2.4 GHz @ 20 MHz**

Data rate	MCS 0 Mbps	MSC 7 Mbps	MSC 8 Mbps	MSC 15 Mbps
Receiver sensitivity	-87 dBm	-69 dBm	-86 dBm	-68 dBm
Transmit power	17 dBm	13 dBm	17 dBm	13 dBm

**IEEE 802.11n 2.4 GHz @ 40 MHz**

Data rate	MCS 0 Mbps	MSC 7 Mbps	MSC 8 Mbps	MSC 15 Mbps
Receiver sensitivity	-84 dBm	-65 dBm	-86 dBm	-65 dBm
Transmit power	17 dBm	13 dBm	17 dBm	13 dBm

**IEEE 802.11a**

Data rate	6 Mbps	54 Mbps
Receiver sensitivity	-86 dBm	-71 dBm
Transmit power	15 dBm	11 dBm

**IEEE 802.11b**

Data rate	1 Mbps	11 Mbps
Receiver sensitivity	-96 dBm	-87 dBm
Transmit power	17 dBm	17 dBm

**IEEE 802.11g**

Data rate	6 Mbps	54 Mbps
Receiver sensitivity	-87 dBm	-72 dBm
Transmit power	17 dBm	13 dBm

**HPE OfficeConnect M220 802.11n (AM) Access Point (J9798A)**

**MCS Index**

**800 nS**

**400 nS**

	20 MHz Rate (Mbps)	40 MHz Rate (Mbps)	20 MHz Rate (Mbps)	40 MHz Rate (Mbps)
0	6.5	13.5	7.2	15
1	13	27	14.4	30
2	19.5	40.5	21.7	45
3	26	54	28.9	60
4	39	81	43.3	90
5	52	108	57.8	120
6	58.5	121.5	65	135
7	65	135	72.2	157.5
8	13	27	14.4	30
9	26	54	28.9	60
10	39	81	43.3	90

**QuickSpecs**

**HPE OfficeConnect M220 802.11n Access Point Series**

**Technical Specifications**

11	52	108	57.8	120
12	78	162	86.7	180
13	104	216	115.6	240
14	117	243	130	270
15	130	270	144.4	300

**HPE OfficeConnect M220 802.11n (WW) Access Point (J9799A)**

<b>Ports</b>	1 RJ-45 autosensing 10/100/1000 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only			
<b>AP characteristics</b>	<b>Radios</b>	802.11a/b/g/n		
	<b>Radio operation modes</b>	Client access, Client bridge		
	<b>AP operation modes</b>	Autonomous		
	<b>Wi-Fi Alliance Certification</b>	a/b/g/n Wi-Fi Certified		
	<b>Physical characteristics</b>	<b>Dimensions</b>	7.62(w) x 5(d) x 1.5(h) in (19.35 x 12.7 x 3.81 cm)	
	<b>Weight</b>	0.75 lb (0.34 kg)		
	<b>Enclosure</b>	Indoor		
<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)		
	<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C), noncondensing		
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)		
	<b>Nonoperating/Storage relative humidity</b>	15% to 95% @ 149°F (65°C), noncondensing		
	<b>Altitude</b>	up to 15,000 ft (4.6 km)		
	<b>Acoustic</b>	Low-speed fan: 0 dB, High-speed fan: 0 dB (no fan)		
<b>Electrical characteristics</b>	<b>Description</b>	IEEE 802.3af PoE Compliant or included 110-240 V 50/60 Hz external power supply		
	<b>Voltage</b>	100 - 240 VAC, rated		
	<b>Current</b>	0.4 A		
	<b>Maximum power rating</b>	4.8 W		
	<b>PoE power</b>	7 W PoE		
	<b>Notes</b>	PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS). 5.3 watts is the maximum power draw when the device is used with the included power adapter.		
<b>Frequency band and operating channels</b>	<b>European Union</b>	2.412 - 2.472 GHz (13 channels)		
		5.180 - 5.240 GHz (4 channels)		
		5.500 - 5.700 GHz (8 channels)		
	<b>Rest of World (Actual channels designated by selecting country in UI)</b>	2.412 - 2.472 GHz (13 channels)		
		5.180 - 5.240 GHz (4 channels)		
		5.260 - 5.320 GHz (4 channels) 5.500 - 5.700 GHz (11 channels) 5.745 - 5.825 GHz (5 channels)		

**QuickSpecs**

**HPE OfficeConnect M220 802.11n Access Point Series**

**Technical Specifications**

<b>Radio</b>	FCC Part 15.247; FCC Part 15.407 (no DFS); RSS-210, Issue 8; RSS-Gen, Issue 3
<b>Safety</b>	UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition
<b>RF Exposure</b>	Canada RSS-102; FCC Bulletin OET-65 Supplement C
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

**HPE OfficeConnect M220 802.11n (WW) Access Point (J9799A)**

**IEEE 802.11n 5 GHz @ 20 MHz**

Data rate	MCS 0 Mbps	MSC 7 Mbps	MSC 8 Mbps	MSC 15 Mbps
Receiver sensitivity	-86 dBm	-67 dBm	-86 dBm	-68 dBm
Transmit power	15 dBm	11 dBm	15 dBm	11 dBm

**IEEE 802.11n 5 GHz @ 40 MHz**

Data rate	MCS 0 Mbps	MSC 7 Mbps	MSC 8 Mbps	MSC 15 Mbps
Receiver sensitivity	-83 dBm	-64 dBm	-84 dBm	-65 dBm
Transmit power	15 dBm	11 dBm	15 dBm	11 dBm

**IEEE 802.11n 2.4 GHz @ 20 MHz**

Data rate	MCS 0 Mbps	MSC 7 Mbps	MSC 8 Mbps	MSC 15 Mbps
Receiver sensitivity	-87 dBm	-69 dBm	-86 dBm	-68 dBm
Transmit power	17 dBm	13 dBm	17 dBm	13 dBm

**IEEE 802.11n 2.4 GHz @ 40 MHz**

Data rate	MCS 0 Mbps	MSC 7 Mbps	MSC 8 Mbps	MSC 15 Mbps
Receiver sensitivity	-84 dBm	-65 dBm	-86 dBm	-65 dBm
Transmit power	17 dBm	13 dBm	17 dBm	13 dBm

**IEEE 802.11a**

Data rate	6 Mbps	54 Mbps
Receiver sensitivity	-86 dBm	-71 dBm
Transmit power	15 dBm	11 dBm

**IEEE 802.11b**

Data rate	1 Mbps	11 Mbps
Receiver sensitivity	-96 dBm	-87 dBm
Transmit power	17 dBm	17 dBm

**IEEE 802.11g**

Data rate	6 Mbps	54 Mbps
Receiver sensitivity	-87 dBm	-72 dBm
Transmit power	17 dBm	13 dBm

**HPE OfficeConnect M220 802.11n (WW) Access Point (J9799A)**

**MCS Index**

**800 nS**

**400 nS**

	20 MHz Rate (Mbps)	40 MHz Rate (Mbps)	20 MHz Rate (Mbps)	40 MHz Rate (Mbps)
0	6.5	13.5	7.2	15
1	13	27	14.4	30
2	19.5	40.5	21.7	45



**QuickSpecs**

**HPE OfficeConnect M220 802.11n Access Point Series**

---

**Technical Specifications**

3	26	54	28.9	60
4	39	81	43.3	90
5	52	108	57.8	120
6	58.5	121.5	65	135
7	65	135	72.2	157.5
8	13	27	14.4	30
9	26	54	28.9	60
10	39	81	43.3	90
11	52	108	57.8	120
12	78	162	86.7	180
13	104	216	115.6	240
14	117	243	130	270
15	130	270	144.4	300

**Summary of Changes**

<b>Date</b>	<b>Version History</b>	<b>Action</b>	<b>Description of Change:</b>
01-Aug-2016	From Version 6 to 7	Changed	Adding #AC3 Option on Configuration section.  Minor edits on Overview and Technical Specifications.
06-May-2016	From Version 5 to 6	Changed	Document name changed to HPE OfficeConnect M220 802.11n Access Point Series. Changes made on technical Specifications and Overview. SKU descriptions updated.
01-Dec-2015	From Version 4 to 5	Changed	Updated Overview and Technical Specifications
01-Dec-2014	From Version 3 to 4	Changed	Warranty and support updated
18-Aug-2014	From Version 2 to 3	Changes	Content Edits
16-Oct-2013	From Version 1 to 2	Changed	Updated the specifications for both models, removing external antennas.

## Summary of Changes



**Sign up for updates**

---

© Copyright 2016 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

Microsoft is a U.S. registered trademark of the Microsoft group of companies.

c04123152 - 14448 - Worldwide - V7 - 1-August-2016



**Hewlett Packard  
Enterprise**